

Technical Specifications

<i>Minimum Specification Required</i>	
Brand Model	
Quantity	48 units
Type	Enduro, off-road
Engine:	
Displacement in ccm:	not less than 240 ccm and up to 300 ccm
Cooling:	Air-cooled / Liquid cooled
Valve Configuration	single-cylinder four valve, DOHC
Max Power	max. 40ps/9,000rpm
Starter	Electric
Drive train:	
Transmission	five or six-speed, manual
Chassis / suspension / brakes:	
Front Suspension	fully adjustable leading-axle
Rear Suspension	single shock with spring;
Front Brake	single hydraulic disc
Rear Brake	single hydraulic disc or drum
Front Tire	off-road/enduro tire with tube, 80 to 90/90 to 100-21
Rear Tire	off-road/enduro tire with tube, 100 to 120/80 to 90-19
Dimensions:	
Trail	100 to 150 mm
Wheelbase	1400 to 1490 mm
Seat Height	870 to 980 mm
Kerb Weight	100 to 150 kg
Fuel tank capacity	more than 7,5l
Ground Clearance	no less than 240 mm (front) - no less than 260mm (back)
Other	
Licence and Safety	License and testing protocol for European/Ukrainian markets available
Colors	Black, White, Green, Red
Warranty:	One year, transferable, unlimited mileage limited warranty.

